

Ideal for servers, video surveillance, and other demanding write-intensive applications, WD RE4 7200 RPM Enterprise SATA hard drives offer up to 2 TB capacity, 64 MB cache, 4th generation vibration tolerance and 5-year limited warranty.





WD RE4

Enterprise SATA Hard Drives



Product Features

Massive capacity

WD RE4 Enterprise SATA drives are available with up to 2 TB of cavernous capacity.

Dual processor

With double the processing power, WD RE4 boasts the highest performance of any drive in the RE family.

RAFF™

Enhanced RAFF technology includes sophisticated electronics to monitor the drive and correct both linear and rotational vibration in real time. The result is a significant performance improvement in high vibration environments over the previous generation of drives.

Dual actuator technology

A head positioning system with two actuators that improves positional accuracy over the data track(s). The primary actuator provides coarse displacement using conventional electromagnetic actuator principles. The secondary actuator uses piezoelectric motion to fine tune the head positioning to a higher degree of accuracy. (2 TB only)

StableTrac[™]

The motor shaft is secured at both ends to reduce system-induced vibration and stabilize platters for accurate tracking during read and write operations.

IntelliSeek™

Calculates optimum seek speeds to lower power consumption, noise, and vibration

Multi-axis shock sensor

Automatically detects the subtlest shock events and compensates to protect the data

RAID-specific, time-limited error recovery (TLER)

Prevents drive fallout caused by the extended hard drive error-recovery processes common to desktop drives.

NoTouch™ ramp load technology

The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit.

Thermal extended burn-in test

Each drive is put through extended burn-in testing with thermal cycling to ensure reliable operation.

Third generation dynamic fly

Each read-write head's fly height is adjusted in real time for optimum reliability.

Product Specifications

INTERFACE

SATA 3 Gb/s

MODELS

WD2003FYYS WD1503FYYS WD1003FBYX WD5003ABYX WD2503ABYX FORM FACTOR

3.5-inch

CAPACITIES

2 TB 1.5 TB 1 TB 500 GB 250 GB SPIN SPEED 7200 RPM

MTBF

1.2 million hours at 100% duty cycle

CACHE

64 MB

LIMITED WARRANTY

5 years

Western Digital, WD, the WD logo and Put Your Life On It are registered trademarks in the U.S. and other countries; IntelliSeek, NoTouch, RAFF and StableTrac are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Pictures shown may vary from actual product. Not all products may be available in all regions of the world. All product and packaging specifications subject to change without notice. © 2010 Western Digital Technologies, Inc. All rights reserved.

As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second