



12TB | 7200 RPM | SATA 6Gb/s and SAS 12Gb/s

Highlights

- 12TB capacity¹ in a standard 3.5-inch form factor
- PMR technology works with all capacity enterprise applications & environments
- Reliable, field-proven, 4th generation design
- Outstanding power efficiency (Watts/TB)
- Compared to 8TB Ultrastar air drives
 - 50% more capacity
 - 52% more power efficient (Watts/TB)
 - 25% more reliable (MTBF)
- SATA 6Gb/s and SAS 12Gb/s
 - 12Gb/s SAS compatible with next-gen data centers; backwards compatible with 6Gb/s SAS
- 2.5M hours MTBF² rating & 5-year limited warranty
- Instant Secure Erase (ISE) & Self-Encrypting Drive (SED) options
- Advanced Format 4Kn and 512e models

Applications/Environments

- Enterprise and data center applications where capacity density, power efficiency and reliability are paramount
- Cloud & Hyperscale storage
- Massive scale-out (MSO), high-density data centers
- Distributed File Systems
- Bulk storage using object storage solutions like CEPH™ and OpenStack Swift
- Primary and secondary storage for Hadoop® to support Big Data Analytics
- Centralized video surveillance
- Ideal for all mainstream enterprise capacity applications

More Value to the Data Center with Maximum Capacity, Power Efficiency and Reliability

Laying the foundation for a worry-free data center, Western Digital delivers capacity to conquer the data explosion – Ultrastar® DC HC520, previously known as Ultrastar He¹² and part of our HC500 series of helium-filled hard drives. Designed to handle workloads up to 550TB per year, the Ultrastar DC HC520 is the industry's first 12TB drive and uses traditional perpendicular magnetic recording (PMR) technology to make it drop-in ready for any enterprise-capacity application or environment. The stable internal environment created by fourth-generation HelioSeal® technology enables a new 8-disk design, increasing the capacity by 20% when compared to the 7-disk design of the prior generation, Ultrastar DC HC510. This high capacity helium drive offers one of the lowest power profiles in the industry to help data center architects meet eco-environmental goals and requirements. Targeted at 2.5M hours MTBF, the Ultrastar DC HC520 provides the highest reliability rating available of all HDDs on the market today by building on the successful design of its 10TB, 8TB and 6TB predecessors. Trust Western Digital and the Ultrastar DC HC520 to deliver more capacity, more efficiency, more reliability and more value to your data center.

HelioSeal Technology Helps Solve Challenges Facing Next Generation Data Centers

Data centers are facing growing pressures. Data volume is expanding, operating costs are rising, yet budgets remain flat. Lowering the total cost of ownership (TCO) has become the focus of data center architects and the Ultrastar DC HC520 provides the best value proposition and greatest storage efficiency available. Compared to 8TB Ultrastar air-filled drives, this HelioSeal hard drive provides 50% more capacity, uses 52% less power (Watts/TB), and is 25% more reliable, rated at 2.5M hours MTBF. Data-center ready features like a second generation dual-stage actuator—the Western Digital Micro Actuator—enhance head-positioning accuracy to deliver better performance, data integrity and overall drive reliability, especially in multi-drive environments where operational vibration is present. Refer to our technical brief to learn more. A choice of 6Gb/s SATA and 12Gb/s SAS interface enables easy integration into high performance data centers.

Data Durability and Data Security to Support Compliance and Privacy Requirements

As drive capacity grows beyond single-digit TBs, object storage systems with erasure coding provide better data durability compared to RAID systems, given its tolerance for simultaneous error conditions. The Ultrastar DC HC520 is a best-fit for object storage implementations with its massive capacity and unbeaten reliability rating. Compliance and privacy requirements drive the need for increased data security. The Ultrastar DC HC520 offers security and encryption options to help protect data from unauthorized use, including TCG SAS models.

Western Digital Quality and Service

The Ultrastar DC HC520 extends Western Digital's long-standing tradition of reliability leadership with a 2.5M-hour MTBF rating and a 5-year limited warranty. Ultrastar quality, capacity, power efficiency, and world-class technical support and service provides customers with a lower total cost of ownership over previous generations. Western Digital data center drives are backed by an array of technical support and services, which may include customer and integration assistance. Western Digital is dedicated to providing a complete portfolio of products and services to help create environments for data to thrive.

50%

MORE CAPACITY*

52%

LOWER WATTS/TB*

25%

MORE RELIABLE*

* compared to 8TB air-filled Ultrastar hard drives

Features & Benefits

Feature / Function	Benefits
Capacity	<ul style="list-style-type: none"> • 12TB • Provides 50% more capacity than 8TB drives
Power Efficiency	<ul style="list-style-type: none"> • Ultra-low Watts per terabyte (W/TB) • 52% lower idle W/TB than 8TB Ultrastar air-filled drives
Performance	<ul style="list-style-type: none"> • Dual-Stage Micro Actuator • Rotational Vibration Safeguard (RVS) • Media Cache Plus architecture • Rebuild Assist mode • SATA 6Gb/s & SAS 12Gb/s • 256MB cache buffer • More accurate head positioning, especially in multi-drive environments, for better performance, data integrity and reliability • Maintains drive performance in high rotational vibration environments and multi-drive systems • Better random write performance • Dramatically improves RAID recovery time and maintains system performance during recovery • Provides compatibility with high-performance data centers • Improves response time and data management
Reliability	<ul style="list-style-type: none"> • Dual safe firmware • 2.5M hours MTBF² and 0.35% AFR² • 5-year limited warranty • Retains previous firmware version for safe firmware updates, verified with an RSA signature • Industry's highest reliability rating for Capacity • Enterprise HDD for fewer failures/less service needs • Industry's best for enterprise-class hard drives
Data Security	<ul style="list-style-type: none"> • Instant Secure Erase • Encryption options on SAS models • Enables swift and efficient drive redeployment and retirement • Hardware-based encryption protects data from unauthorized use (TCG SAS options)

Specifications

	SATA Models	SAS Models
Model No.	HUH721212ALE60y HUH721212ALN60y	HUH721212AL420y HUH721212AL520y
Configuration		
Interface	SATA 6Gb/s	SAS 12Gb/s
Capacity ¹ (TB)	12TB	←
Format: Sector size ³ (bytes)	4Kn: 4096 512e: 512	4Kn: 4096, 4112, 4160, 4224 512e: 512, 520, 528
Max. Areal density (Gbits/sq. in.)	864	←
Performance		
Data buffer ⁴ (MB)	256	←
Rotational speed (RPM)	7200	←
Latency average (ms)	4.16	←
Interface transfer rate (MB/s, max)	600	1200
Sustained transfer rate ⁵ (MiB/s, typical)	243	←
(MB/s, typical)	255	←
Reliability		
Error rate (non-recoverable, bits read)	1 in 10 ¹⁵	←
Load/Unload cycles (at 40°C)	600,000	←
Availability (hrs/day x days/wk)	24x7	←
MTBF ² (M hours)	2.5	←
Annualized Failure Rate ² (AFR)	0.35%	←
Warranty (yrs)	5	←

¹ One megabyte (MB) is equal to one million bytes, one gigabyte (GB) is equal to 1,000MB (one billion bytes), and one terabyte (TB) is equal to 1,000GB (one trillion bytes) when referring to storage capacity. Accessible capacity will vary from the stated capacity due to object storage methodologies, formatting, system software, and other factors.

² MTBF and AFR specifications are based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions for this drive model.

MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

³ Advanced Format drive: 4K (4096-byte) physical sectors

⁴ Portion of buffer capacity used for drive firmware

⁵ MiB/s is 2²⁰ bytes, MB/s is 10⁶ bytes

⁶ Excludes command overhead

⁷ SATA models: 8KB Queue Depth = 1 @ 40 IOPS, SAS models: 4KB Queue Depth = 4 @ Max IOPS

⁸ Idle specification is based on use of Idle_A

	SATA Models	SAS Models
Acoustics		
Idle (Bels, typical)	2.0/3.6	←
Power		
Requirement	+5 VDC, +12VDC	←
Operating ⁷	6.9	10.1
Idle ⁸ (W)	5.0	6.1
Power consumption efficiency at Idle (W/TB)		
(Watts/TB)	0.42	0.51
(Watts/GB)	0.00042	0.00051
Physical size		
z-height (mm)	26.1	←
Dimensions (width x depth, mm)	101.6 (+/-0.25) x 147	←
Weight (g, max)	660	←
Environmental (Operating)		
Ambient temperature	5° to 60° C	←
Shock half-sine wave 2 ms, G)	70	←
Vibration (G RMS 5 to 500 Hz)	0.67 (XYZ)	←
Environmental (Non-Operating)		
Ambient temperature	-40° to 70° C	←
Shock (half-sine wave, G)	300 (2ms) / 150 (11ms)	←
Random vibration (G RMS 2 to 200 Hz)	1.04 (XYZ)	←

NOTE: See "How to read the Ultrastar model number" below for possible values for xx and y.

How to Read the Ultrastar Model Number

Example: HUH721212AL420y = 7200 RPM, 12TB, 4Kn SAS 12Gb/s

H = Western Digital	42 = Interface, 4Kn SAS 12Gb/s
U = Ultrastar	(52 = 512e SAS 12Gb/s,
H = Helium (vs. S for Standard)	E6 = 512e SATA 6Gb/s,
72 = 7200 RPM	N6 = 4Kn SATA 6Gb/s)
12 = Full capacity—12TB (12,000GB)	0 = Reserved
xx = Capacity this model	y = Data Security Mode
12TB (12,000GB)	0 = Instant Secure Erase
A = Generation code	1 = Self-encrypting Drive (SAS)
L = 26.1mm z-height	4 = Secure Erase (overwrite only)
	5 = TCG encryption with FIPS (SAS)

Western Digital.

5601 Great Oaks Parkway
San Jose, CA 95119, USA
US (Toll-Free): 800.801.4618
International: 408.717.6000

www.wdc.com/dc-hc520

© 2016–19 Western Digital Corporation or its affiliates. All rights reserved. Produced 12/16, rev 8/19. Western Digital, the Western Digital logo, HelioSeal and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. Other marks are property of their respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Please visit the Support section of our website, www.westerndigital.com for additional information on product specifications. Pictures shown may vary from actual products.