



# Ultrastar® SSD800MM

## Highlights

- MLC NAND Flash for ultra-high performance and endurance
- Endurance: 10 drive writes per day (DW/D) for five years
- Best IOPS/Watt for reduced TCO
- 12Gb/s SAS interface for maximum throughput
- Advanced power loss data management technology
- Self-encrypting models conform to TCG's Enterprise specification

## Applications/Environments

- Ultra-high performance tier-0 enterprise storage
- Enterprise-class servers and high performance computing
- Space and/or power constrained environments
- Online Transaction Processing (OLTP)
- Video pre/post-production
- Financial and e-commerce
- Database analytics



800GB, 400GB and 200GB | MLC  
2.5-inch SFF | SAS 12Gb/s

## Maximum Performance, Reliability and Endurance

The Ultrastar SSD800MM delivers high sequential throughput, up to 1200MB/s read and 700MB/s write (12Gb/s SAS). The Ultrastar SSD800MM also delivers up to 145,000 read and 70,000 write IOPS, reaching speeds >100 times faster than HDDs and double the speed of current 6Gb/s SSDs, allowing rapid access to “hot” enterprise data for improved productivity and operational efficiency. The Ultrastar SSD800MM family offers significant value in terms of IOPS per Watt, while reducing total cost of ownership (TCO) through low power consumption, efficient cooling and reduced space requirements.

The Ultrastar SSD800MM family combines enterprise-grade MLC NAND flash memory, advanced endurance management firmware and power loss data management techniques to extend reliability, endurance, and sustained performance over the life of the SSD. The Ultrastar SSD800MM family achieves an extraordinary 0.44% annual failure rate (AFR) or two million hour mean-time-between-failure (MTBF). The 800GB capacity model endures up to 14.6 Petabytes (PB) of random writes over the life of the drive—the equivalent of writing 8 Terabytes (TB) per day for five years.

For complete end-to-end data protection and reliability, the Ultrastar SSD800MM family incorporates the T10 Data Integrity Field (DIF) standard, extended error correction code (ECC), Exclusive-OR (XOR) parity to protect against flash die failure, parity-checked internal data paths without an external write cache, and an exclusive power loss data management feature that does not require supercapacitors. The Ultrastar SSD800MM family is backed by a five year limited warranty, or the maximum Petabytes (PB) written (based on capacity).

## HGST Enterprise Storage Experience

HGST leverages decades of proven enterprise storage expertise in Serial Attached SCSI (SAS) design reliability, firmware, customer qualification and system integration to the Ultrastar® SSD800MM solid-state drive (SSD) family. The synergistic relationship between HGST's throughput-enhancing SSDs and traditional HDDs provides cost effective, end-to-end enterprise-class storage solutions, delivering reliability, compatibility, capacity, cost and system performance. This combination makes HGST a leading SSD/HDD provider with the experience and technology needed to meet escalating reliability, endurance and performance in the most demanding enterprise environments.

## HGST Quality and Service

HGST's Ultrastar SSD800MM family extends the company's long-standing tradition of performance and reliability leadership. A balanced combination of new and proven technologies enables high reliability and availability to customer data.

HGST drives are backed by an array of technical support and services, which may include customer and integration assistance. HGST is dedicated to providing a complete portfolio of SSD/HDD solutions to satisfy today's monumental computing needs.

## Features & Benefits

	Performance	Power	Capacity	Reliability	Integration
Feature/function	<ul style="list-style-type: none"> <li>• SAS 12Gb/s</li> <li>• MLC NAND flash memory</li> <li>• 1150MB/s / 700MB/s sequential R/W</li> <li>• 145K / 70K IOPS random R/W</li> <li>• 110K IOPS on 70/30 mix R/W</li> </ul>	9.0 and 11.0 Watt options	<ul style="list-style-type: none"> <li>• 800GB</li> <li>• 400GB</li> <li>• 200GB</li> </ul>	<ul style="list-style-type: none"> <li>• 0.44% AFR (2M hours MTBF)</li> <li>• 1E-17 bit error rate</li> <li>• T10 end-to-end data protection</li> <li>• Exclusive-OR (XOR) NAND</li> <li>• Power loss data management</li> <li>• Unlimited reads, up to 14.6PB random writes (800GB)</li> </ul>	<ul style="list-style-type: none"> <li>• HDD architecture commonality</li> <li>• Systems integration and test lab</li> </ul>
Benefit	<ul style="list-style-type: none"> <li>• 6Gb/s Active-Active Dual Port or 12Gb/s Single/ Dual port for enhanced reliability</li> <li>• Highest write performance and endurance</li> <li>• Maximum throughput and IOPS for ultra-fast access to data; &gt;100x faster than typical HDD</li> </ul>	Improved performance with higher power option	More capacity for less space and power	<ul style="list-style-type: none"> <li>• Reduced field replacement effort</li> <li>• Enhanced error detection and correction for optimal data integrity</li> <li>• Protection against flash die failure</li> <li>• Assures data integrity during power failure</li> <li>• Maximum endurance over the life of SSD</li> </ul>	<ul style="list-style-type: none"> <li>• Compatibility with Ultrastar SAS HDDs</li> <li>• Extensive interoperability and compliance testing</li> </ul>



# Ultrastar® SSD800MM

## Specifications

<b>Model / Part No.</b>	HUSMM8080ASS200 / OB28589 HUSMM8040ASS200 / OB28588 HUSMM8020ASS200 / OB28587 HUSMM8080ASS201 / OB28592 HUSMM8040ASS201 / OB28591 HUSMM8020ASS201 / OB28590 HUSMM8080ASS204 / OB30108 HUSMM8040ASS204 / OB30107 HUSMM8020ASS204 / OB30106 HUSMM8080ASS205 / OB30228 HUSMM8040ASS205 / OB30227 HUSMM8020ASS205 / OB30226
<b>Configuration</b>	
Interface	SAS 12Gb/s
Capacity (GB <sup>1</sup> ) at 512 bytes/sector	800 / 400 / 200
Form factor	2.5-inch
Flash memory technology	Multi Level Cell (MLC)
<b>Performance</b>	
Read throughput (max MB/s, sequential 64K)	1150
Write throughput (max MB/s, sequential 64K)	700
Read IOPS (max IOPS, random 4K)	145,000
Write IOPS (max IOPS, random 4K)	70,000
<b>Reliability</b>	
Error rate (non-recoverable, bits read)	1 in 10 <sup>17</sup>
MTBF <sup>2</sup> (M hours)	2.0
Availability (hrs/day x days/wk)	24x7
Endurance (max PB <sup>1</sup> , random write)	14.6 / 7.3 / 3.7

© 2014-2015 HGST, a Western Digital company, 3403 Yerba Buena Road, San Jose, CA 95135 USA. Produced in the United States 8/14, revised 8/15. All rights reserved.

Ultrastar is a registered trademark of HGST, Inc. and its affiliates in the United States and/or other countries.

HGST trademarks are intended and authorized for use only in countries and jurisdictions in which HGST has obtained the rights to use, market and advertise the brand. Contact HGST for additional information. HGST shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

### Power

Requirement	+5 VDC (+/-5%) +12VDC (+/-5%)
Operating (W)	9.0 and 11.0
Idle (W)	2.2 / 2.1 / 2.1

### Physical

z-height (mm, max)	15.0
Dimensions (width x depth, mm)	70.1 x 100.6
Weight (g, typical)	164

### Environmental (operating)

Ambient temperature	0° to 60° C
Shock (half-sine wave)	1000G (0.5ms) 500G (2ms)
Vibration, random (G RMS)	2.16, all axes (5 to 700 Hz)

<sup>1</sup>One gigabyte (GB) is equal to one billion bytes, one terabyte (TB) is equal to 1,000GB (one trillion bytes), and one petabyte (PB) is equal to 1,000TB (one quadrillion bytes) when referring to solid-state drive or hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the drive, the computer's operating system, and other factors.

<sup>2</sup>MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under nominal operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.

### How to Read the Ultrastar Model Number

HUSMM8080ASS200 = 800GB, SAS 12Gb/s  
 H = HGST  
 U = Ultrastar  
 S = Standard  
 MM = Multi level cell, mainstream endurance (10DW/D)  
 80 = Full capacity (800GB)  
 80 = Capacity of this model (80 = 800GB, 40 = 400GB, 20 = 200GB)  
 A = Generation code  
 S = Small form factor (vs. L for Large FF)  
 S2 = Interface, SAS 12Gb/s  
 0 = Reserved  
 O = Crypto sanitize (1 = TCG encryption, 4 = No encryption, 5 = TCG + FIPS certified encryption)

References in this publication to HGST's products, programs or services do not imply that HGST intends to make these available in all countries in which it operates.

Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary.

Please visit the Support section of our website [www.hgst.com/support](http://www.hgst.com/support) for additional information on product specifications. Photographs may show design models.

### Information & Technical Support

[www.hgst.com](http://www.hgst.com)  
[www.hgst.com/support](http://www.hgst.com/support)

**Partners First Program**  
[channelpartners@hgst.com](mailto:channelpartners@hgst.com)  
[www.hgst.com/partners](http://www.hgst.com/partners)