

mSATA

Solid-State Drive

Modular Embedded Storage with Maximum Data Integrity

With its industry-standard SATA interface, small footprint and high performance, HGST's mSATA solid-state drive is an ideal storage solution for space-constrained, low power applications requiring high reliability.

Serial ATA (SATA) continues to replace parallel ATA (PATA) in embedded systems, where small-format SATA storage designs are increasingly important. With up to 80 percent lower power consumption, mSATA SSDs are a logical drop-in replacement for conventional HDD storage, and provide an excellent option for tiered storage in embedded systems.

Low-Power, Small Footprint Embedded Storage

HGST's embedded SATA SSDs provide the advanced flash management technology and data integrity of HGST's industry-leading enterprise SSDs in small-form factors designed for space-constrained applications. They provide flexible, low- power, and small-capacity solutions that are ideal for embedded systems.

Features and Benefits

Feature / Function	Benefits
High Performance	6Gbps SATA interface provides fast data throughput with zero latency
Rugged Design	Supports embedded applications in harsh environments: high shock, vibration and industrial temperature (-40° to 85° C)
Data Integrity	Advanced error-checking and correction (ECC) algorithms protect data against common bit errors
High Endurance	Total drive wear-leveling algorithm increases the useful life of flash up to 10x over the manufacturer's stated useful life
Simple Integration	Compliant to the JEDEC MO-300A/B specification supporting drop-in implementation
High Reliability	Integrated bad block management and error handling improves data integrity. PowerSafe technology protects against drive corruption as a result of unexpected power loss
Advanced Flash Controller Technology	Provides unmatched performance, reliability and data integrity in embedded applications



Information and Technical Support

www.hgst.com (Main Web site)
www.hgst.com/partners (Partner Web site)

North America

support_usa@hgst.com
Toll free: 1 888 426-5214, Direct: 1 408 717-8087

Asia Pacific

support_ap@hgst.com / 65 6840 9595

EMEA and UK

support_uk@hgst.com / 44 20 7133 0032

Germany

support_uk@hgst.com / 49 6929 993601

Program Support

Partners First Program channelpartners@hgst.com

Specifications

Models	s260 mSATA (SLC)	s260 mSATA (eMLC)	s265 mSATA mini
Interface			
Capacity	16/32/64GB	50/100/200GB	8/16GB
Type	SATA (6Gbps)	SATA (6Gbps)	SATA (6Gbps)
Form Factor	mSATA (JEDEC MO-300A)	mSATA (JEDEC MO-300A)	mSATA (JEDEC MO-300B)
Performance			
Average Response Time	<12ms	<12ms	<12ms
Transfer Rate (Read)	Up to 500MB/s	Up to 500MB/s	Up to 300MB/s
Transfer Rate (Write)	Up to 250MB/s	Up to 150MB/s	Up to 150MB/s
Endurance	10X drive writes/day, 5-years	10X drive writes/day, 3-years	10X drive writes/day, 5-years
MTBF	4 million hours	4 million hours	4 million hours
Physical			
Dimensions (L x W x H)	50mm X 30mm X 4.8mm	50mm X 30mm X 4.8mm	26mm X 30mm X 3.8mm
Power	<1.5W @ 3.3V	<1.5W @ 3.3V	<1.5W @ 3.3V
Environmental			
Operational Temperature	-40°C to 85°C	0°C to 70°C	-40°C to 85°C
Humidity (non-condensing)	5% to 95%	5% to 95%	5% to 95%
Shock / Vibration	350G / 20G	350G / 20G	350G / 20G
Altitude	-1,000 to 80,000 ft	-1,000 to 80,000 ft	-1,000 to 80,000 ft
Compliance			
	RoHS-6, EU Directive	RoHS-6, EU Directive	RoHS-6, EU Directive

¹ One GB is equal to one billion bytes when referring to hard drive capacity. Accessible capacity will vary depending on the operating environment and formatting.

² Portion of buffer capacity used for drive firmware

³ MB is equal to MillionBytes

⁴ Excludes command overhead

⁵ MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.

© 2013 HGST, Inc., 3403 Yerba Buena Road, San Jose, CA 95135 USA. Produced in the United States 04/13. All rights reserved. Other trademarks are the property of their respective companies.

HGST trademarks are intended and authorized for use only in countries and jurisdictions in which HGST has obtained the rights to use, market and advertise the brand. Contact HGST for additional information. HGST shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

References in this publication to HGST's products, programs, or services do not imply that HGST intends to make these available in all countries in which it operates. Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary.

Please visit the Support section of our website, www.hgst.com/support, for additional information on product specifications. Photographs may show design models.

One GB is equal to one billion bytes and one TB equals 1,000 GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the hard drive, the computer's operating system, and other factors.

MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.