

MACH16™ Slim SATA

Embedded SSD

A True Enterprise-Class SSD for the Embedded Market


The new MACH16™ Slim SATA Embedded SSD provides embedded system designers and Original Equipment Manufacturers (OEMs) with the same advanced flash management technology as HGST's market-leading enterprise SSDs.

MACH16 SSD technology has been extended to embedded system design with one of the industry's smallest solid-state solution formats. In addition to its small format, the MACH16 Slim SATA Embedded SSD can leverage industry-standard 22-pin SATA cabling (JEDEC MO-297 and SFF-8156 specifications) in order to provide the highest data integrity, endurance and reliability available in this market segment.

Through sustained performance of up to 245MB/s for sequential 128K read operations, and up to 150MB/s for sequential 128K write operations, MACH16 Slim SATA is ideally suited for a range of embedded applications, including rugged PCs, casino gaming, transportation systems, ATM machines, kiosks, point-of-sale machines, printers, vehicle infotainment systems, data loggers and medical equipment.

Features and Benefits

Feature / Function	Benefits
PowerSafe™ Technology	Provides instant data backup and recovery in the event of an unplanned power failure
Secure Array of Flash Elements™ (SAFE) Technology	Improves reliability by providing mechanisms for recovery from NAND flash page, block, die and chip failures that improve the Mean Time Between Failure (MTBF) and the Mean Time To Data Loss (MTTDL)
CellCare™ Technology	Combines flash management techniques, digital signal processing, ECC methods and other technologies to increase NAND cell endurance, data retention and performance
Advanced SSD controller and firmware	Optimizes performance, endurance, data integrity and reliability of the embedded SSD
Predictive read optimization	Minimizes loss of performance over the useful life of the MACH16 Slim SATA
Data-path protection	Protects critical data from corruption
Advanced error correction	Measures and manages flash media wear
Advanced wear Leveling	Spreads the writing of each data block evenly across all data blocks for consistent and even use of NAND blocks, ensuring that one block location does not wear out faster than any other block location



A True Enterprise-Class SSD for the Embedded Market

MACH16 Slim SATA delivers the features required for enterprise computing and other mission-critical applications where downtime is not an option.

Information and Technical Support

www.hgst.com (Main Web site)
www.hgst.com/partners (Partner Web site)

North America

support_usa@hgst.com
Toll free: 1 888 426-5214, Direct: 1 408 717-8087

Asia Pacific

support_ap@hgst.com / 65 6840 9595

EMEA and UK

support_uk@hgst.com / 44 20 7133 0032

Germany

support_uk@hgst.com / 49 6929 993601

Program Support

Partners First Program channelpartners@hgst.com

Specifications

Interface	
Type	SATA II (3Gbps)
Capacity (GB) ¹	25 / 50
Form Factor	Slim SATA (MO-297)
Performance	
Average Response Time	<16ms
Transfer Rate (Read)	Up to 245MB/s
Transfer Rate (Write)	Up to 150MB/s
Transactional Performance (Read IOPS)	24,000 (random)
Transactional Performance (Write IOPS)	5,000 (random)
MTBF	5 million hours
Physical	
Dimensions (mm)	54mm (L) X 39mm (W) X 4mm (H)
Power	4W
Power Supply	5V or 3.3V
Acoustics	
Idle (Bels, typical)	2.9
Environmental	
Operational Temperature	-40° to 85°C
Non-Operating Temperature	-55° to 95°C
Shock/Vibration	350G/20G
Humidity (non-condensing)	5% to 95%
Altitude	-1,000 to 80,000 ft.
Compliance	
	UL, FCC, CE, C-Tick, CSA, VCCI, EIP, RoHS-6

¹ One GB is equal to one billion bytes when referring to hard drive capacity. Accessible capacity will vary depending on the operating environment and formatting.

² Portion of buffer capacity used for drive firmware
³ MB is equal to MillionBytes

⁴ Excludes command overhead

⁵ MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.

© 2013 HGST, Inc., 3403 Yerba Buena Road, San Jose, CA 95135 USA. Produced in the United States 03/13. All rights reserved. Other trademarks are the property of their respective companies.

HGST trademarks are intended and authorized for use only in countries and jurisdictions in which HGST has obtained the rights to use, market and advertise the brand. Contact HGST for additional information. HGST shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

References in this publication to HGST's products, programs, or services do not imply that HGST intends to make these available in all countries in which it operates. Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary.

Please visit the Support section of our website, www.hgst.com/support, for additional information on product specifications. Photographs may show design models.

One GB is equal to one billion bytes and one TB equals 1,000 GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the hard drive, the computer's operating system, and other factors.

MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.