



OpenFlex™ Data24 NVMe-oF™ Storage Platform

The Performance of NVMe™ Flash in Shared Storage

Western Digital's OpenFlex™ Data24 NVMe-oF™ storage platform extends the high performance of NVMe™ flash to shared storage. It provides low-latency sharing of NVMe SSDs over a high-performance Ethernet fabric to deliver similar performance to locally attached NVMe SSDs. Unsurpassed connectivity in its class using Western Digital RapidFlex™ NVMe-oF controllers, allows up to six hosts to be attached without a switch, like a traditional JBOF.

NVMe-over-Fabrics, or NVMe-oF, is a networked storage protocol that allows storage to be disaggregated from compute to make that storage widely available to multiple applications and servers. By enabling applications to share a common pool of storage capacity, data can be easily shared between applications or needed capacity can be allocated to an application to respond to application needs.

OpenFlex Data24 NVMe-oF storage platform can also be used as a disaggregated storage resource in an open composable infrastructure environment using the Open Composable API. The platform can also be specified with just two RapidFlex adapters for simpler environments and as a direct replacement for SAS external storage. OpenFlex Data24 is built to deliver high availability and enterprise-class reliability. The entire platform, including SSDs, is backed with a 5-year limited warranty.

Features

- Up to 368TB¹ of low latency Dual Port SSDs in 2U 24-bay platform
- Bandwidth match between SSDs (Storage) and I/O (Network) – No oversubscription
- RESTful API support for simplified management
- Vertically integrated Western Digital design: NVMe SSDs, fabric adapters and platform
- Optional dual adapter configuration for direct SAS replacement
- Industry-leading 5-year limited warranty

Benefits

- Enables multiple servers to share NVMe flash storage as if it were local
- Leverages low latency fabric to fully utilize IOPS and capacity
- Provides more efficient use of large capacity SSDs at low latency
- Balances access to eliminate over-subscription and maintain NVMe performance
- Provides open composability thru mature NVMe-oF standard
- Ideal SAS replacement option (dual adapter configuration)

¹ One terabyte (TB) is equal to one trillion bytes. Actual user capacity may be less due to operating environment.

OpenFlex™ Data24 NVMe-oF™ Storage Platform

PRODUCT BRIEF

Specifications

Hardware	Specifications	OpenFlex Data24
<ul style="list-style-type: none">• 24 Dual port high-performance SSDs	Form Factor	2U
<ul style="list-style-type: none">• Wide range of NVMe SSD capacity and endurance options<ul style="list-style-type: none">—UltraStar® DC SN840: 1DWPD: Up to 15360 GB—UltraStar DC SN840: 3DWPD: Up to 6400 GB	Front Drive Bays	Up to 24 x U.2 NVMe SSDs
<ul style="list-style-type: none">• High availability with dual IOM	Power Supply	2x 2000W Platinum (Titanium Optional) 200–240VAC, CRPS, Hot Plug
<ul style="list-style-type: none">• 3 PCIe® x 16 slots/IOM	Fabric Adapter Slots	6x PCIe x16
<ul style="list-style-type: none">• Western Digital RapidFlex NVMe-oF fabric adapters<ul style="list-style-type: none">—Six 100GbE ports with dual IOM for maximum performance—Two 100GbE ports for direct replacement of SAS external storage	Fabric Adapter(s)	Western Digital RapidFlex NVMe-oF Fabric Adapter
<ul style="list-style-type: none">• Two 100GbE ports for direct replacement of SAS external storage	Cabling	Passive (1 – 5m) and Active Optical (5 – 50m)
<ul style="list-style-type: none">• Western Digital RapidFlex NVMe-oF fabric adapters	Platform Management	ARM Based BMC
<ul style="list-style-type: none">• OpenFlex inspired composability in a mainstream 2U24	Rear I/O	1G-BASE-T Management Port (RJ-45)
<ul style="list-style-type: none">• 28" (711mm) chassis depth – fits most commonly used short depth racks (800 – 1000 mm)	HA Redundancy	Dual IOMs, Dual Port SSDs, Dual PSUs, Dual Rotor Hot Plug Fans
	Environmental	10°C – 35°C
	Chassis Dimensions (Height x Width x Depth)	8.75 x 44.80 x 71.12 cm 3.45" x 17.64" x 28" in
	Weight	Maximum 31.75 kg / 70 lb
	Limited Warranty	5 Years Standard

Performance

		128K Bandwidth	4K IOPS	4K QD1 Latency
6 x 100GbE	Read	71.3 GB/s	15.2M	168 µs
	Write	39.8 GB/s	6.2M	44 µs
2 x 100GbE	Read	23.83 GB/s	5.09M	175.45 µs
	Write	15.09 GB/s	3.72M	41.73 µs

Western Digital

5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com

© 2022 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital logo, OpenFlex, RapidFlex, and UltraStar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. The NVMe and NVMe-oF word marks are trademarks of NVM Express, Inc. PCIe® is a registered trademark and/or service mark of PCI-SIG in the United States and/or other countries. All other marks are the property of their respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications and do not constitute a warranty. Actual specifications for unique part numbers may vary. Pictures shown may vary from actual products.