



Ultrastar® Data60 60-Bay Hybrid Storage Platform

The Next Generation Hybrid Platform for Software-Defined Storage

Delivers High Density and Flexibility

The Ultrastar Data60 is a key element of next-generation disaggregated storage and software-defined storage (SDS) systems, delivering high density and the flexibility to balance performance with cost. The Ultrastar® Data60 provides up to 1.2PB¹ of raw storage using our 20TB HDDs in a compact and efficient form factor. Western Digital HelioSeal® drives ensure cool running, quiet operation and high reliability.

Building on 50+ Years of Storage Design Experience

Conventional dense disk shelves frequently suffer from performance degradation due to induced vibration from adjacent drives. Traditional platforms also have cooling challenges as the cooling air passes over successive rows of drives, losing effectiveness as it gets heated up along the airflow path. Developing storage devices and platforms side-by-side, we address these challenges through Silicon to Systems Design, a set of technologies developed based on a holistic view of devices, platform, and their interactions. The first two of these innovative technologies are IsoVibe™ and ArcticFlow™. IsoVibe reduces vibration-induced performance degradation, while ArcticFlow overcomes the cooling issues by introducing cool air into the middle of the platform. Both these technologies contribute to long-term reliability, enabling our five-year limited warranty on the entire platform.

Designed for Government


Mission goals and nimble planning require highly scalable and secure data storage infrastructure. Ultrastar Data60 addresses the demanding storage needs of institutions that require dense, shared HDD storage. Ultrastar Data60 provides the flexibility to balance capacity, performance and cost and to be deployed as part of a highly scalable and secure storage infrastructure. Available TAA compliance allows this product to be sold via specific government channels and FIPS 140-2 validated drives offer increased assurances for secure environments.

Highlights

- FIPS 140-2 Inside* available supports highly secure environments
- TAA compliant models enable optimal government sourcing options
- Up to 60 Ultrastar HDDs (SAS or SATA)
- Up to 1.2PB of raw storage in 4U using 20TB HDDs
- Choose dual-port SAS for high availability or single-port SATA for low cost
- 4 rack units, 712mm depth
- Up to 12 × 12Gb/s SAS-3 host connections
- Up to 4 units may be daisy-chained for a total raw capacity of 4.8PB
- Patented IsoVibe technology ensures maximum performance even in heavy workloads
- Enterprise-grade redundant and hot-swappable PSUs, IO Modules and fans
- Improved cooling from innovative ArcticFlow technology
- Rack-mounted top cover for quick and easy service
- 5-year limited warranty

* For specific models





IsoVibe

IsoVibe Patented Vibration Isolation Technology

Precise cuts in the baseboard provide a suspension for the drives in the chassis, isolating them from transmitted vibration. The result is that consistent performance is maintained, even when all the drives are working hard.



ArcticFlow

ArcticFlow Thermal Zone Cooling Technology

By introducing cool air into the center of the chassis, drives operate at lower and more consistent temperatures than conventional systems. This results in lower fan speeds, reduced vibration, lower power consumption, quieter operation and ultimately higher reliability.



Resource Manager

Western Digital Resource Manager

A GUI-based tool that enables real-time monitoring and management of the platform and provides a consolidated dashboard displaying the most critical information. Other views allow platform configuration, health monitoring and maintenance.

Max Drives	<ul style="list-style-type: none"> • 60 × 3.5" drive bays
Drive Interface	<ul style="list-style-type: none"> • 12Gb/s SAS • 6Gb/s SATA
Available Drive Capacities	<ul style="list-style-type: none"> • HDD up to 20TB CMR or up to 20TB SMR
Host Interface	<ul style="list-style-type: none"> • Dual redundant I/O Modules (IOM) • 6 Mini-SAS HD ports per IOM
Weight	<ul style="list-style-type: none"> • Product without drives: 27.3kg (60lbs) • Product with 60 HDDs: 79.4kg (175lbs)
LED Indicators	<ul style="list-style-type: none"> • Front/Rear: Power, ID, Fault • Drive: Activity, Fault
Physical Dimensions	<ul style="list-style-type: none"> • Height: 175mm (6.89") • Width: 447mm (17.61") • Depth: 712mm (28.03") • Depth in Rack: Max of 890mm (35.04") with dual CMA—includes 2 SAS cables
Management	<ul style="list-style-type: none"> • SCSI Enclosure Services • Redfish (out of band, via RJ45)
Power	<ul style="list-style-type: none"> • Dual 1600W or 1800W, 80+ Platinum • 200–240V AC input, auto ranging, 50–60Hz
Cooling	<ul style="list-style-type: none"> • 4 main enclosure fans, front-to-rear system cooling with zero-loss backflow prevention • 1 IO module fan • Dual PSUs with built-in fans
Environmental	<ul style="list-style-type: none"> • Operating Temperature: 5°C to 35°C • Non-op Temperature: -40°C to 70°C • Humidity: 5 to 85% relative humidity • Operating Altitude: -300m to 3048m (-984 ft to 10,000 ft) • Sound Power: < 7.2Bels @ 23±2°C
Serviceability	<ul style="list-style-type: none"> • Cable-free hot-swappable IOM, power supply, fans and drives

¹ One terabyte (TB) is equal to one trillion bytes and one petabyte (PB) is equal to 1,000TB. Actual user capacity may be less due to operating environment.

Western Digital.

5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com

© 2022 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital logo, ArcticFlow, HelloSeal, IsoVibe, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. FIPS TM: A Certification Mark of NIST, which does not imply product endorsement by NIST, the U.S. or Canadian Governments. All other marks are the property of their respective owners. References in this publication to Ultrastar products, programs or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications and do not constitute a warranty. Actual specifications for unique part numbers may vary. Pictures shown may vary from actual products. Please visit our website, westerndigital.com/platforms for additional information on product specifications.