



Ultrastar® Edge Transportable Edge Server

High-Performance Server for Remote Location Data Capture and Processing

Western Digital Ultrastar® Edge is a high-performance edge server that enables organizations to deploy remote data capture and analytics at the cloud edge. Processing data closer to where it is generated reduces the latency associated with sending data from a remote location to the core for processing. Remote processing reduces the amount of traffic on network backbones, enables faster decision making and helps keep data center costs in check.

The ability to have low-latency processing in remote locations can enhance project or mission productivity. Organizations can deliver data center cloud-like services without an external network connection. The server has 40 cores, a GPU, 512 GiB of memory and over 60TB of Ultrastar NVMe flash storage, so applications that normally run on IaaS environments can easily be run remotely.

With a wheeled travel case, the Ultrastar Edge is easily transportable between locations and rack-mountable with the included rail kit when needed. A militarized and ruggedized version, Ultrastar Edge-MR, is also available.

Designed for Government

Available TAA compliance allows this product to be sold via specific government channels. FIPS 140-2 drive models (validation in progress) with the Trusted Platform Module architecture offer increased assurances for secure environments.

Highlights

- FIPS 140-2 drive models (validation in progress) available and includes TPM v2.0 module to accommodate the most secure environments
- TAA compliant enables optimal government sourcing options
- Extreme performance with 40 CPU cores and
- 512 GiB memory¹
- Graphical processor unit for AI/ML tasks
- Over 60TB of NVMe™ flash storage²
- High-performance 100 GbE networking
- Trusted Platform Module 2.0 for security
- Robust transport case with wheels and handle

Specifications

Max Drives	<ul style="list-style-type: none"> • 8 Ultrastar DC SN640 NVMe SSDs • 7.68 TB per SSD, 1 DW/D, ISE (Instant Secure Erase)
Boot Drives	<ul style="list-style-type: none"> • 2 M.2 NVMe 1TB SSDs
CPUs	<ul style="list-style-type: none"> • 2 Intel® Xeon® Gold 6230T, 2.1 GHz, 20 cores each, 125 W TDP
Memory	<ul style="list-style-type: none"> • 512 GiB DDR4 Installed (8x 64 GiB DIMMs)
GPU	<ul style="list-style-type: none"> • NVIDIA® Tesla® T4
Networking	<ul style="list-style-type: none"> • Dual 10GBase-T RJ-45 • Mellanox® ConnectX®-5 100 GbE QSFP28
I/O	<ul style="list-style-type: none"> • 1 Serial DB9 Console Port
Physical Dimensions	<ul style="list-style-type: none"> • Height: 88.9mm (3.5") • Width: 431.8mm (17") • Depth: 502.9mm (19.8")
Weight	<ul style="list-style-type: none"> • 15.15 kg (33.4 lbs)
Power	<ul style="list-style-type: none"> • 850 W, Platinum • 100–240 V AC input, auto ranging, 50–60 Hz
Cooling	<ul style="list-style-type: none"> • 460 mm fans
Management	<ul style="list-style-type: none"> • IPMI 2.0 system management • Dedicated DB9 Serial management port
Environmental	<ul style="list-style-type: none"> • Operating Temperature: 0° C to 43° C • Non-op Temperature: -5° C to 63° C • Operating Altitude: 3,050 m (10,000 ft)
Physical Security	<ul style="list-style-type: none"> • FIPS 140–2 Level 2

¹ System memory is indicated in gibibytes (GiB) and one GiB is equal to 1,073,741,824 bytes.

² One terabyte (TB) is equal to one trillion bytes and one petabyte (PB) is equal to 1,000TB. Actual user capacity may be less due to operating environment.

Western Digital.

5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com

© 2022 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital logo, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. Intel and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. Mellanox and ConnectX are registered trademarks of Mellanox Technologies, Ltd. NVIDIA and Tesla are registered trademarks of NVIDIA Corporation. The NVMe word mark is a trademark of NVM Express, Inc. All other marks are the property of their respective owners. References in this publication to Ultrastar products, programs or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications and do not constitute a warranty. Actual specifications for unique part numbers may vary. Pictures shown may vary from actual products.